



LR65566

Tel: (450) 449-0412 ; 1-866-540-0412 Fax: (450)449-9115 ; 1-866-499-9115

SÉRIE DC SERIES



DE PIÈCE / PART # : DC _ _ _ _ YZ



E153598

SPÉCIFICATIONS ÉLECTRIQUES / ELECTRICAL SPECIFICATIONS

SERIE/SERIES DC

VUE DE DESSOUS / BOTTOM VIEW
TYPE FERMÉ / CLOSED TYPE

* 25VA@750VA

** 1000VA@6000VA

PHASE:

1

FREQ.:

50/60 Hz.

***60 Hz.

CLASSE ISOL.

*B(130°C)

INSUL. CLASS

**H(180°C)

ELEV. TEMP.

* < 80°C

TEMP. RISE

** < 120°C

NIV. DE BRUIT

SOUND LEVEL

< 40 dB.

TENSION / YZ / VOLTAGE

- | | |
|---|--------------------------------------|
| <input type="checkbox"/> A = 12 | <input type="checkbox"/> J = 347 |
| <input type="checkbox"/> B = 24 | <input type="checkbox"/> K = 380 |
| <input type="checkbox"/> C = 12/24 | <input type="checkbox"/> L = 347/380 |
| <input type="checkbox"/> D = 16/32 | <input type="checkbox"/> M = 416 |
| <input type="checkbox"/> E = 120 | <input type="checkbox"/> N = 208/416 |
| <input type="checkbox"/> F = 208 | <input type="checkbox"/> O = 480*** |
| <input type="checkbox"/> G = 240 | <input type="checkbox"/> P = 240/480 |
| <input type="checkbox"/> H = 120/240 | <input type="checkbox"/> Q = 600*** |
| <input type="checkbox"/> I = 277 | <input type="checkbox"/> S = _____ |
| <input type="checkbox"/> U = 480/600*** | |




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

SPÉCIFICATIONS MÉCANIQUES / MECHANICAL SPECIFICATIONS: (dimensions = pouces/inches).

VA	0025	0050	0100	0150	0200	0250	0350	0500	0750	1000	1500	2000	2500	3000	4000	5000	6000	
A	3.06	3.06	3.75	3.75	3.75	4.50	4.50	5.25	5.25	7.50	7.50	7.50	9.00	9.00	9.00	9.00	9.00	
B	5.16	5.55	6.18	6.38	6.88	6.60	7.60	8.60	9.60	8.60	8.80	9.80	11.25	11.25	12.25	13.25	14.25	
C	2.86	2.86	3.54	3.55	3.50	4.12	4.12	4.75	4.75	6.57	6.57	6.57	7.83	7.83	7.83	7.83	7.83	
D MTG	1.75	1.75	2.50	2.50	2.50	2.50	2.50	3.75	3.75	5.00	5.00	5.00	6.97	6.97	6.97	6.97	6.97	
E MTG	3.62	4.00	4.50	4.75	5.28	5.00	6.00	7.00	8.00	7.10	7.10	8.10	9.38	9.38	10.4	11.4	12.4	
F MTG	0.25*0.50					0.25*0.63					0.28*0.62							
LBS	1.95	2.82	4.60	5.37	6.89	9.30	12.9	15.6	20.9	30.2	36.2	47.1	66.9	66.9	85.2	101	115	
KG	0.89	1.30	2.09	2.44	3.13	4.22	5.86	7.08	9.48	13.7	16.4	21.3	30.4	30.4	38.7	45.7	52	

Toutes les dimensions sont approximatives. Spécifications peuvent changer sans préavis. All dimensions and weights are approximate. Specifications may change without notice.

TRANSFAB 
magnetic solutions

NUMÉRO DE MODÈLE:

MODEL NUMBER:

DC _ _ _ _ YZ

ZONE	REV	REVISION	DESCRIPTION	DATE	APPROVAL APPROB.	Dessiné par: Drawn by: SS	DWG NO. 71CUDCR5	REV 05
------	-----	----------	-------------	------	---------------------	------------------------------	---------------------	-----------

DATE: JANUARY/30/08

PAGE: 1 de 1