

V1K Open

PART NUMBER	RATED VOLTS	NEC HP 480V	NEC HP 600V	NEC HP 240V	AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	WATTS LOSS	WEIGHT
V1K2A00	600	0.75	1	–	2	9	5.5	7.25	TB	10	LB-IN	75	8
V1K3A00	600	1 – 1.5	2	0.5	3	9	5.5	7.25	TB	10	LB-IN	75	8
V1K4A00	600	2	3	0.75	4	9	5.5	7.25	TB	10	LB-IN	75	8
V1K6A00	600	3	–	1 – 1.5	6	9	5.5	7.25	TB	10	LB-IN	80	8
V1K8A00	600	5	5	2	8	9	5.5	7.25	TB	10	LB-IN	90	8
V1K12A00	600	7.5	10	3	12	9	5.5	7.25	TB	10	LB-IN	95	8
V1K16A00	600	10	–	5	16	9	5.5	8.25	TB	20	LB-IN	95	12
V1K18A00	600	10	15	–	18	9	5.5	8.25	TB	20	LB-IN	110	12
V1K21A00	600	15	–	–	21	9	5.5	8.25	TB	20	LB-IN	110	12
V1K25A00	600	15	20	7.5	25	9	5.5	8.25	TB	20	LB-IN	110	12
V1K27A00	600	20	25	–	27	9	5.5	8.25	TB	20	LB-IN	110	14
V1K35A00	600	25	30	10	35	12	8	9	TB	30	LB-IN	130	17
V1K45A00	600	30	40	15	45	12	8	9	TB	30	LB-IN	135	17
V1K55A00	600	40	50	20	55	12	8	9	TB	35	LB-IN	145	16
V1K80A00	600	50 – 60	75	25 – 30	80	12	8	9	TB	35	LB-IN	255	23
V1K110A00	600	75	100	40	110	12	8	10.25	PT	50	LB-IN	245	40
V1K130A00	600	100	125	50	130	8.5	11	9.5	PT	50	LB-IN	270	55
V1K160A00	600	125	150	60	160	8.5	11	10.5	PT	375	LB-IN	260	60
V1K200A00	600	150	200	75	200	8.5	11	10.25	PT	50	LB-IN	265	60
V1K250A00	600	200	250	100	250	8.5	11	10.25	PT	50	LB-IN	290	65
V1K305A00	600	250	300	–	305	8.75	11	12.25	PT	500	LB-IN	325	80
V1K362A00	600	300	350	150	362	8.5	11.75	12	PT	375	LB-IN	300	80
V1K420A00	600	350	450	–	420	10	11.75	13.75	PT	500	LB-IN	450	95
V1K480A00	600	400	500	200	480	10	11.75	13.75	PT	500	LB-IN	475	100
V1K600A00	600	500	600	–	600	12.75	15	13.75	PT	500	LB-IN	515	130
V1K750A00	600	600	700	–	750	12.75	15	14.75	PT	500	LB-IN	770	135