

V1K Type 1

PART NUMBER	RATED VOLTS	NEC HP 480V	NEC HP 600V	NEC HP 240V	AMPS	HEIGHT	WIDTH	DEPTH	ENCL TYPE	TERM TYPE	TERM TORQUE	TORQUE UM	WATTS LOSS
V1K2A01	600	0.75	1	–	2	9	5.5	10	1	tb	10	LB-IN	75
V1K3A01	600	1 – 1.5	2	0.5	3	9	5.5	10	1	TB	10	LB-IN	75
V1K4A01	600	2	3	0.75	4	9	5.5	10	1	TB	10	LB-IN	75
V1K6A01	600	3	–	1 – 1.5	6	9	5.5	10	1	TB	10	LB-IN	80
V1K8A01	600	5	5	2	8	9	5.5	10	1	TB	10	LB-IN	90
V1K12A01	600	7.5	10	3	12	9	5.5	10	1	TB	10	LB-IN	95
V1K16A01	600	10	–	5	16	9	5.5	10	1	TB	20	LB-IN	95
V1K18A01	600	10	15	–	18	9	5.5	10	1	TB	20	LB-IN	110
V1K21A01	600	15	–	–	21	9	5.5	10	1	TB	20	LB-IN	110
V1K25A01	600	15	20	7.5	25	9	5.5	10	1	TB	20	LB-IN	110
V1K27A01	600	20	25	–	27	9	5.5	10	1	TB	20	LB-IN	110
V1K35A01	600	25	30	10	35	12	8	11.5	1	TB	30	LB-IN	130
V1K45A01	600	30	40	15	45	12	8	11.5	1	TB	30	LB-IN	135
V1K55A01	600	40	50	20	55	12	8	11.5	1	TB	35	LB-IN	145
V1K80A01	600	50 – 60	75	25 – 30	80	12	8	11.5	1	TB	35	LB-IN	255
V1K110A01	600	75	100	40	110	16.5	18	15	1	PT	50	LB-IN	245
V1K130A01	600	100	125	50	130	16.5	18	15	1	PT	50	LB-IN	270
V1K160A01	600	125	150	60	160	16.5	18	15	1	PT	375	LB-IN	260
V1K200A01	600	150	200	75	200	16.5	18	15	1	PT	50	LB-IN	265
V1K250A01	600	200	250	100	250	16.5	18	15	1	PT	50	LB-IN	290
V1K305A01	600	250	300	–	305	16.5	18	30	1	PT	500	LB-IN	325
V1K362A01	600	300	350	150	362	16.5	18	30	1	PT	375	LB-IN	300
V1K420A01	600	350	450	–	420	16.5	18	30	1	PT	500	LB-IN	450
V1K480A01	600	400	500	200	480	16.5	18	30	1	PT	500	LB-IN	475
V1K600A01	600	500	600	–	600	16.5	18	30	1	PT	500	LB-IN	515
V1K750A01	600	600	700	–	750	16.5	18	30	1	PT	500	LB-IN	770