

V1K Type 3R

| PART NUMBER | RATED VOLTS | NEC HP 480V | NEC HP 600V | NEC HP 240V | AMPS | HEIGHT | WIDTH | DEPTH | ENCL TYPE | TERM TYPE | TERM TORQUE | TORQUE UM | WATTS LOSS |
|-------------|-------------|-------------|-------------|-------------|------|--------|-------|-------|-----------|-----------|-------------|-----------|------------|
| V1K2A03 | 600 | 0.75 | 1 | – | 2 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 75 |
| V1K3A03 | 600 | 1 – 1.5 | 2 | 0.5 | 3 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 75 |
| V1K4A03 | 600 | 2 | 3 | 0.75 | 4 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 75 |
| V1K6A03 | 600 | 3 | – | 1 – 1.5 | 6 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 80 |
| V1K8A03 | 600 | 5 | 5 | 2 | 8 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 90 |
| V1K12A03 | 600 | 7.5 | 10 | 3 | 12 | 11.45 | 10 | 12 | 3R | TB | 10 | LB-IN | 95 |
| V1K16A03 | 600 | 10 | – | 5 | 16 | 11.45 | 10 | 12 | 3R | TB | 20 | LB-IN | 95 |
| V1K18A03 | 600 | 10 | 15 | – | 18 | 11.45 | 10 | 12 | 3R | TB | 20 | LB-IN | 110 |
| V1K21A03 | 600 | 15 | – | – | 21 | 11.45 | 10 | 12 | 3R | TB | 20 | LB-IN | 110 |
| V1K25A03 | 600 | 15 | 20 | 7.5 | 25 | 11.45 | 10 | 12 | 3R | TB | 20 | LB-IN | 110 |
| V1K27A03 | 600 | 20 | 25 | – | 27 | 11.45 | 10 | 12 | 3R | TB | 20 | LB-IN | 110 |
| V1K35A03 | 600 | 25 | 30 | 10 | 35 | 19.18 | 15.62 | 19.5 | 3R | TB | 30 | LB-IN | 130 |
| V1K45A03 | 600 | 30 | 40 | 15 | 45 | 19.18 | 15.62 | 19.5 | 3R | TB | 30 | LB-IN | 135 |
| V1K55A03 | 600 | 40 | 50 | 20 | 55 | 19.18 | 15.62 | 19.5 | 3R | TB | 35 | LB-IN | 145 |
| V1K80A03 | 600 | 50 – 60 | 75 | 25 – 30 | 80 | 19.18 | 15.62 | 19.5 | 3R | TB | 35 | LB-IN | 255 |
| V1K110A03 | 600 | 75 | 100 | 40 | 110 | 19.18 | 15.62 | 19.5 | 3R | PT | 50 | LB-IN | 245 |
| V1K130A03 | 600 | 100 | 125 | 50 | 130 | 19.18 | 15.62 | 19.5 | 3R | PT | 50 | LB-IN | 270 |
| V1K160A03 | 600 | 125 | 150 | 60 | 160 | 19.18 | 15.62 | 19.5 | 3R | PT | 375 | LB-IN | 260 |
| V1K200A03 | 600 | 150 | 200 | 75 | 200 | 19.18 | 15.62 | 19.5 | 3R | PT | 50 | LB-IN | 265 |
| V1K250A03 | 600 | 200 | 250 | 100 | 250 | 19.18 | 15.62 | 19.5 | 3R | PT | 50 | LB-IN | 290 |
| V1K305A03 | 600 | 250 | 300 | – | 305 | 22.15 | 20.62 | 28.5 | 3R | PT | 500 | LB-IN | 325 |
| V1K362A03 | 600 | 300 | 350 | 150 | 362 | 22.15 | 20.62 | 28.5 | 3R | PT | 375 | LB-IN | 300 |
| V1K420A03 | 600 | 350 | 450 | – | 420 | 22.15 | 20.62 | 28.5 | 3R | PT | 500 | LB-IN | 450 |
| V1K480A03 | 600 | 400 | 500 | 200 | 480 | 22.15 | 20.62 | 28.5 | 3R | PT | 500 | LB-IN | 475 |
| V1K600A03 | 600 | 500 | 600 | – | 600 | 36 | 28.21 | 36.86 | 3R | PT | 500 | LB-IN | 515 |
| V1K750A03 | 600 | 600 | 700 | – | 750 | 36 | 28.21 | 36.86 | 3R | PT | 500 | LB-IN | 770 |